

## 600 SERIES POWER SUPPLY/CHARGERS

### Single Output

#### AL600ULX

- UL Listed in the U.S. and Canada for Access Control. UL Listed in the U.S. for Fire. CSFM Approved.
- 6 amp @ 12VDC or 24VDC.
- Single non power-limited output.
- Fits two (2) 12VDC/7AH batteries.

Enclosure dimensions: 13.5"H x 13"W x 3.25"D

#### AL600ULXD

- UL Listed in the U.S. and Canada for Access Control. UL Listed in the U.S. for Fire. CE Approved.
- Selectable Input 115VAC or 220VAC.
- 6 amp @ 12VDC or 24VDC.
- Single non power-limited output.
- Fits two (2) 12VDC/12AH batteries.

Enclosure dimensions: 15.5"H x 12.23"W x 4.5"D



66

#### Features:

- 115VAC 60Hz. input.
- Filtered and electronically regulated output(s).
- Short circuit and thermal overload protection.
- Built-in charger for sealed lead acid or gel type batteries.
- Zero voltage drop upon transfer to battery backup.
- Automatic switch over to stand-by battery when AC fails.
- AC fail, low battery and battery presence supervision.
- AC input and DC output LED indicators.
- Includes cam lock and battery leads.

\* For red enclosure add suffix "R" to model number.

